

KEY FEATURES

SHORT MOTOR CONSTRUCTION


- Cast Iron Block
- Wet Liners
- Fully Floating Pistons
- Nodular Iron Crankshaft
- High Volume Oil Pump
- High Volume Oil Sump

CYLINDER HEAD

- Cast Iron Cylinder Head
- Adjustable Rocker Arms
- Rubber Valve Gasket

CONSTRUCTION

- Heavy Duty Design
- High Volume Cooling System
- Simple, Maintenance Free, High Pressure Fuel System
- Direct Injection Combustion Chamber
- P Type Injectors
- High Flow Fuel, Oil & Donaldson Air Filters



MAXIMUM POWER RATING - For 'HP' MULTIPLY x 1.34

Power Output Rated 122kW @ 2600rpm

Model	1800rpm	2000rpm	2300rpm	2600rpm
DP6700T	105kW	113kW	119kW	122kW

PRODUCT CHARACTERISTICS



DESIGN & QUALITY

BKB Group firepump engines offer industry leading value for money. Proven quality and Australian design, powering over thousands of firepumps nationwide. All engines come backed by a 2 year warranty and are constructed to last. When the job needs to be done, you can rely on BKB Engines to perform.



SERVICE KITS

All engines can be supplied with service kits. All parts used in service are readily available, high quality parts including Donaldson filters. Kits provide a complete ready package for servicing. Included in the kits are belt set, hose kit and all filters; oil, primary and secondary fuel and air cleaners.



CONTROLLER

The BKB Group diesel engine control system delivers simplicity and reliability. Proudly Australian designed and built to AS2941-2013 (Fixed Fire-Pumpset Systems). Available in 12V & 24V. Monitors, displays and records diesel engine information. The construction incorporates high quality industrial components and an advanced microprocessor controller.

DESIGN SPECIFICATIONS	
Model	DP6700T
Type	Inline 6 Cylinder - 2 Valve P/Cyl - OHV
Fuel	Direct Injection - Inline Pump - Electric Governor
Bore/Stroke	105 x 125
Capacity	6.5Ltr
Compression	16:5:1
Intake	Turbocharged
Cooling	Water
Voltage	24V
Min Speed	850rpm
Max Speed	2600rpm

SERVICE INFORMATION	
Fuel Filter	Donaldson P550127
Oil Filter	Donaldson P550965
Air Filter	Donaldson C105003
Oil Capacity	18 Ltrs
Recommended Battery - Min	600CCA x 2 / 90A/H x 2
Bell Housing	SAE3
Cooling System Capacity	19ltrs
Drive	SAE 11.5"
Service Interval	First Service at 12month/ 150hrs then each 12month/250Hours
Coolant	Min 40% Glycol Mix
Oil Type	15W40 - SAE30

POWER PACK PRODUCED WITH:	
<ul style="list-style-type: none"> ▪ Compliance with AS2941-2013 ▪ Oil Pressure Sender & Temp Sender ▪ SAE 11.5" Flywheel ▪ Mounting Feet ▪ Belt Guard 	<ul style="list-style-type: none"> ▪ Flexible Exhaust Coupling ▪ Condensation Trap & Muffler ▪ Pull to Stop Solenoid ▪ Oil & Coolant ▪ Coolant Jacket Heater

ELECTRICAL	
Starter Motor	24V - 5kW - Reduction Drive
Alternator	24V - 40Amp
Oil Pressure Sender	10 Bar (VDO Compatible)
Temp Sender	30 - 120°C
RPM Sensor	Magnetic Pulse Type - M18 x 1.5
Fuel STOP Solenoid	24V - Pull to Stop - Two Wire - Body Earth

ENGINE SPECIFICATIONS	
Fuel Consumption @ 75% Load - 2200rpm	.240gr/kWhr
Approx Fuel Consumption at 100% load - 2600rpm	34ltrs per/hour
Cooling Water Supply	1.8ltrs/sec@20°C
Intake Air Flow	160ltrs/sec
Exhaust Pipe Size	4"/100mm
Exhaust Flow	560 ltrs/sec
Exhaust Heat Rejection	95kW
Heat Rejection to Atmosphere	17kW
Cooling System Heat Rejection	85kW
Exhaust Temp Max	640°C
Max Exhaust Backpressure	7kPa
Max Coolant Temp	85°C






COOLING SYSTEM	
Type	Heat Exchanger Cooled

ENGINE MOUNTING	
Mounting Bolts	M16

Note:

Variations to engines may be made without notice.

FIREPUMP DP6700T DIESEL POWER PACK HEAT EXCHANGER COOLED



DRAWING TITLE	DP6700T	NOTES: All dimensions are in mm	TOLERANCES:	ADDRESS: 38-40 LICOLA CRES DANDENONG SOUTH VIC 3175 PHONE: 1300 188 477	
SCALE	1:25				
DATE:	27/11/18				
DRAWN BY:					